

a Garlock Hygienic Technologies company

RFSTS



Smoothbore PTFE Lined Hose with Stainless Steel Braid and Clear Silicone Outer Cover

TUBE: Seamless white PTFE

COVER: Braided stainless steel and clear silicone outer cover

TEMPERATURE: -20°F to 350°F

Part Number	Hose ID Inch	Hose OD Inch	Bend Radius Inch	Max. Working Pressure @ 70°F psig	Vacuum Rating @ 70°F in. Hg.	Weight Per Foot
04RFSTS	0.25	0.56	3.00	3000	FULL	0.12
06RFSTS	0.38	0.70	4.00	2000	FULL	0.13
08RFSTS	0.50	0.82	4.00	1425	FULL	0.16
12RFSTS	0.75	1.08	7.00	1000	FULL	0.20
16RFSTS	1.00	1.32	12.00	1000	FULL	0.50
24RFSTS	1.50	1.82	20.00	900	FULL	0.92

Maximum length 20 feet.

Features

- Outer cover is stainless steel braid overwrap with clear silicone cover
- · Silicone cover acts as thermal insulator
- Lining is smooth PTFE inner core, non-stick surface
- Non-stick contact surface will not contaminate contacted substances • Not affected by weather and will not age in service within the
- recommended temperature and pressure ratings
- · Withstands high velocity and pressure surges
- Conductive black liner available
- Ease of cleanability Autoclavable
- Can be steam cleaned

Applications

- Food processingPharmaceutical processing
- Cosmetics
- Hot CIP solutions
- Chemical products · Low pressure steam

Hose Certifications

- USP Class VI
 - FDA 21 CFR 177.1550
 - USDA

26 Brookfield Drive • Sparta, New Jersey 07871 973.579.2959 • 866-442-2959 Toll Free • 973.579.7275 Fax • www.rubberfab.com