

# Rubber Fab

a Garlock Hygienic Technologies company

## Hose Validation Chart

1 = Excellent 2 = Good 3 = Acceptable 4 = Marginal 5 = Poor 0 = Do Not Use

Hose Type	Continuous Steam	Intermittent Steam	Pure Water Ambient	Pure Water Hot	Process Fluids Ambient	Process Fluids Hot	Process Fluids Variable (<0°C - >100°C)	Temperature Range
RFFDAEOC	5	3	1	1	2	3	3	-40°F TO 245°F
RFFDAE	5	3	1	1	2	3	3	-20°F TO 300°F
RFFDAELF	5	3	1	1	2	3	3	-20°F TO 300°F
RFF&B	0	5	1	2	3	2	2	-40°F TO 230°F
RFFDA	0	0	1	2	2	2	0	-40°F TO 180°F
RFFDAC	5	3	1	1	2	2	2	-40°F TO 225°F
RFFDABOC	5	3	1	1	2	2	3	-40°F TO 250°F
RFWDAM	0	0	1	1	0	0	0	-40°F TO 200°F
RFRTPOC	3	2	1	1	1	1	2	-40°F TO 300°F
RFRT	0	4	1	3	1	2	4	-40°F TO 300°F
RFRTTP	3	2	1	1	1	1	2	-20°F TO 300°F
RFST	1	1	1	1	1	1	1	-20°F TO 350°F
RFSTB	1	1	1	1	1	1	1	-20°F TO 350°F
RFSF	2	1	1	1	1	1	2	-100°F TO 450°F
RFTFP	4	3	1	2	1	1	2	-40°F TO 300°F
RFCTLP	1	1	1	1	1	1	1	-20°F TO 350°F
RFCTLPB	1	1	1	1	1	1	1	-20°F TO 350°F
RFCTLPP	0	0	1	3	1	1	4	-20°F TO 212°F
RFCTLPPB	0	0	1	3	1	1	4	-20°F TO 212°F
RFSSH	1	1	1	1	2	2	2	-400°F TO 800°F
RFSSHT	1	1	1	1	1	1	1	-20°F TO 350°F
RFSG	0	0	1	3	1	2	3	-25°F TO 300°F
RFCSG	4	3	1	2	1	1	2	-25°F TO 300°F
RFPSSG	0	0	1	3	2	3	4	-20°F TO 240°F
RFKMD	4	3	1	2	2	2	3	-40°F TO 240°F
RFSB	4	3	1	2	2	2	3	-100°F TO 350°F
RFSBX	4	3	1	2	2	2	3	-80°F TO 350°F
RFSBHP	4	3	1	2	2	2	3	-100°F TO 350°F
RFS4P	4	3	1	2	2	2	3	-100°F TO 350°F
RFSV	4	3	1	2	2	2	3	-100°F TO 350°F
RFSVOC	4	3	1	2	2	2	3	-100°F TO 350°F
RFPB	0	0	1	3	3	2	0	25°F TO 150°F
RFPVV	0	0	1	3	3	3	0	25°F TO 150°F
RFPVW	0	0	1	3	3	3	0	25°F TO 150°F
RFPC	0	0	1	3	3	3	0	25°F TO 150°F
RFPBW	0	0	1	3	3	3	0	15°F TO 150°F

**NOTE:** Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Rubber Fab. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing. While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice Rubber Fab is a registered trademark for packings, seals, gaskets, and other products of Rubber Fab.