

# Rubber Fab

a Garlock Hygienic Technologies company

## RFRTTP



*Smoothbore Heavy Wall PTFE Lined  
EPDM Rubber Hose*

**TUBE:** Seamless white HEAVY WALL PTFE

**COVER:** EPDM rubber (abrasion resistant)

**REINFORCEMENT:** Multiple braids, helical wire

**TEMPERATURE:** -20°F to 300°F

Part Number	Hose ID Inch	Hose OD Inch	Bend Radius Inch	Max. Working Pressure @ 70°F psig	Vacuum Rating @ 70°F in. Hg.	Weight Per Foot
08RFRTTP	0.53	1.00	1.80	600	FULL	0.46
12RFRTTP	0.78	1.30	2.50	550	FULL	0.56
16RFRTTP	1.03	1.54	3.40	530	FULL	0.79
24RFRTTP	1.52	2.19	5.50	430	FULL	1.22
32RFRTTP	2.02	2.73	8.00	430	FULL	1.84

### Features

- Heavy wall PTFE liner provides good permeation resistance
- Resistant to ozone, chemical, and abrasion
- Double steel wire helix for improved bend radius and shape retention
- Outstanding flexibility
- Non-stick contact surface will not contaminate product
- Inert and resistant to most chemicals and reagents
- Cleanable by CIP, SIP, and COP methods
- Ultra smooth bacteria free tube
- Static grounding available

### Applications

- Pharmaceutical processing
- Chemical transfer
- Hot CIP solutions
- Distillery piping systems
- Fluid transfer
- Food and beverage processing
- Load cells
- Cosmetics

### Hose Certifications

- USP Class VI
- FDA 21 CFR 177.1550
- FDA 21 CFR 177.2600
- 3-A Sanitary Standards



26 Brookfield Drive • Sparta, New Jersey 07871

973.579.2959 • 866-442-2959 Toll Free • 973.579.7275 Fax • [www.rubberfab.com](http://www.rubberfab.com)