

Flex-Pure™ Tri-Clamp Gaskets (EPDM, FKM, VMQ)

Item Number	Nominal diameter DN	Type	Gasket ID** SILICONE	Gasket ID** EPDM and FKM	Tolerance ID	Gasket Outer diameter OD	Tolerance OD	Unit
DIN 11850 (DIN 32676 - DIN 11866 - Row A)								
DIN32676-06-XXX-NG-LE	6	MINI	9,70	9,70	-0/+0,50	21,80	±0,25	mm
DIN32676-08-XXX-NG-LE	8	MINI	10,70	11,20	-0/+0,70	21,80	±0,25	mm
DIN32676-10-XXX-NG-LE	10	Flanged	12,70	12,70	-0/+0,70	34,00	±0,35	mm
DIN32676-15-XXX-NG-LE	15	Flanged	18,20	18,70	-0/+0,70	34,00	±0,35	mm
DIN32676-20-XXX-NG-LE	20	Flanged	22,20	22,70	-0/+0,70	34,00	±0,35	mm
DIN32676-25-XXX-NG-LE	25	Flanged	27,70	27,70	-0/+0,70	50,50	±0,40	mm
DIN32676-32-XXX-NG-LE	32	Flanged	32,70	33,20	-0/+0,70	50,50	±0,40	mm
DIN32676-40-XXX-NG-LE	40	Flanged	38,70	38,70	-0/+0,70	50,50	±0,40	mm
DIN32676-50-XXX-NG-LE	50	Flanged	50,70	50,70	-0/+0,80	64,00	±0,50	mm
DIN32676-65-XXX-NG-LE	65	Flanged	66,20	66,20	-0/+1,00	91,00	±0,50	mm
DIN32676-80-XXX-NG-LE	80	Flanged	81,20	81,20	-0/+1,00	106,00	±0,70	mm
DIN32676-100-XXX-NG-LE	100	Flanged	100,20	100,20	-0/+1,40	119,00	±0,70	mm
DIN32676-125-XXX-NG-LE	125	Flanged	125,20	125,20	-0/+1,40	155,00	±0,70	mm
DIN32676-150-XXX-NG-LE	150	Flanged	150,20	150,20	-0/+1,40	183,00	±0,87	mm
DIN32676-200-XXX-NG-LE	200	Flanged	200,20	200,20	-0/+2,00	233,50	±1,12	mm
ISO 1127 (DIN 32676 - DIN 11866 - Row B)								
ISO1127-06-XXX-NG-LE	6	MINI	10,20	10,20	-0/+0,50	21,80	±0,25	mm
ISO1127-08-XXX-NG-LE	8	MINI	12,00	12,50	-0/+0,70	21,80	±0,25	mm
ISO1127-10-XXX-NG-LE	10	MINI	15,70	15,70	-0/+0,70	21,80	±0,25	mm
ISO1127-15-XXX-NG-LE	15	Flanged	19,80	19,80	-0/+0,70	50,50	±0,40	mm
ISO1127-20-XXX-NG-LE	20	Flanged	24,90	24,90	-0/+0,70	50,50	±0,40	mm
ISO1127-25-XXX-NG-LE	25	Flanged	30,90	30,90	-0/+0,70	50,50	±0,40	mm
ISO1127-32-XXX-NG-LE	32	Flanged	39,10	39,10	-0/+0,70	64,00	±0,50	mm
ISO1127-40-XXX-NG-LE	40	Flanged	45,00	45,00	-0/+0,80	64,00	±0,50	mm
ISO1127-50-XXX-NG-LE	50	Flanged	57,00	57,00	-0/+0,80	77,50	±0,50	mm
ISO1127-65-XXX-NG-LE	65	Flanged	72,30	72,30	-0/+1,00	91,00	±0,50	mm
ISO1127-80-XXX-NG-LE	80	Flanged	84,50	84,50	-0/+1,00	106,00	±0,70	mm
ISO1127-100-XXX-NG-LE	100	Flanged	109,90	109,90	-0/+1,40	130,00	±0,70	mm
ISO1127-125-XXX-NG-LE	125	Flanged	134,70	134,70	-0/+1,40	155,00	±0,70	mm
ISO1127-150-XXX-NG-LE	150	Flanged	163,30	163,30	-0/+1,60	183,00	±0,87	mm
ISO1127-200-XXX-NG-LE	200	Flanged	214,10	214,10	-0/+2,00	233,50	±1,12	mm
ASME BPE (DIN 32676 - DIN 11866 - Row C)								
42XXX-025-NG-LE	¼"	MINI	9,30	9,30	-0/+0,50	21,80	±0,25	mm
42XXX-0375-NG-LE	⅜"	MINI	11,00	11,00	-0/+0,50	21,80	±0,25	mm
42XXX-050-NG-LE	½ "	MINI	12,10	12,60	-0/+0,70	21,80	±0,25	mm
42XXX-075-NG-LE	¾"	MINI	17,00	17,50	-0/+0,70	21,80	±0,25	mm
40XXX-100-NG-LE	1"	Type I	23,30	23,80	-0/+0,70	50,50	±0,40	mm
40XXX-150-NG-LE	1½ "	Type I	35,50	36,00	-0/+0,70	50,50	±0,40	mm
40XXX-200-NG-LE	2"	Type I	48,20	48,20	-0/+0,80	64,00	±0,50	mm
40XXX-250-NG-LE	2½ "	Type I	60,90	60,90	-0/+0,80	77,50	±0,50	mm
40XXX-300-NG-LE	3"	Type I	73,10	73,10	-0/+1,00	91,00	±0,50	mm
40XXX-400-NG-LE	4"	Type I	97,60	97,60	-0/+1,00	119,00	±0,70	mm
40XXX-600-NG-LE	6"	Flanged	147,10	147,10	-0/+1,40	167,00	±0,80	mm
40XXX-800-NG-LE	8"*	Flanged	197,9	197,9	-0/+2,00	217,7	±1,00	mm
40XXX-1000-NG-LE	10"*	Flanged	247,4	247,4	-0/+2,50	268,5	±1,30	mm
40XXX-1200-NG-LE	12"*	Flanged	298,2	298,2	-0/+3,00	319,3	±1,55	mm

* not included in standard

** Rubber Fab optimized the inner diameter (ID) of the gasket to obtain the best possible fit during installation and service when applying 30 in/lbs (3,3 Nm) tightening torque.

NOTE: Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Rubber Fab. Failure to select the proper sealing products could result in property damage and/or serious personal injury. While the utmost care has been used in compiling this data, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Rubber Fab is a registered trademark for packings, seals, gaskets, and other products.

V_09/2022